



## Type EWX-HY-LS (high corrugation)



Cable protection conduit open

### PRODUCT INFORMATION

The EWX-HY-LS cable protection conduits are made of specially modified thermoplastic elastomer. The material is halogen, phosphor and cadmium-free.

With its excellent flexural fatigue strength, this product is ideal for robot technology and in the area of handling systems. For installation of pre-assembled cables, retrofitting or repair of cables. For dynamic applications

involving light to medium mechanical loads. The EWX-HY-LS cable protection conduits have a higher corrugation and feature the following advantages:

- Very good flexibility
- Excellent flexural fatigue strength
- Less wear
- Good crush resistance
- Subsequent installation possible

### SPECIFICATIONS

- Thermoplastic elastomer
- 45 – 160 °C transient / short term  
180 °C
- HB
- > 100000 ~ In conformity with IEC EN 61386

Type	Order No.	Colour	A Ø mm	B Ø mm	R stat. mm	R dyn. mm	Weight kg/100m	Pack m
<b>High corrugation</b>								
EWX-HY-LS 70 <sup>1)</sup>	83122282	Black	64.00	80.00	115.00	235.00	63.00	25
<sup>1)</sup> Min. order quantity 75m								

Suitable for

### MATERIAL PROPERTIES

Thermoplastic elastomer

### THERMAL PROPERTIES

**Temperature / temperature range**  
-45 – 160 °C 180 °C

### FIRE BEHAVIOUR

**Fire classification**  
HB

### MECHANICAL PROPERTIES

**Flexural fatigue strength**  
Cycles: > 100000 ~; Testing method: In conformity with IEC EN 61386; Test value: M32/P29

### APPROVALS AND OPERATING PERMITS

**ROBI approval**

## Type EWX-HY-LS (high corrugation)

### TECHNICAL INFORMATION

**HF** Halogen-free  
DIN 53474

**UV** UV-resistant

### CONFORMITY

**RoHS** RoHS (EC Directive 202/95/EC)

### GENERAL INFORMATION

**Made in Germany** Made in Germany

All details given in our sales material prospectuses and catalogues as well as the information available online are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • prvlD\_96772~20170925~890283~83122282